

## VERTICAL DESIGNS

### 3, 4 and 5-Stage Compressors

- › **Pressure**  
5000 to 7000 psig  
345 to 483 bar
- › **Capacity**  
3.5 to 22 scfm  
100 to 623 l/min
- › **Power**  
5 to 20 hp  
3.7 to 15 kw



**The new Vertical series from the technology leader in high pressure offers space-saving designs suitable for the most demanding requirements.**

Open models offer a budget conscious practical solution while enclosed models can be installed in occupied spaces. Both styles include a full-featured control system for unattended automatic operation. The vertical series offers the perfect continuous-duty rated solutions for a wide variety of applications.

## Vertical Designs

### STANDARD SCOPE OF SUPPLY

- › Multi-stage, air cooled, pressure lubricated, continuous-duty rated reciprocating compressor
- › Electric motor (ODP) with v-belt drive, belt guard and belt tensioning device
- › Automatic condensate drain with condensate collector. Collector includes switch for high condensate level.
- › Automatic operation with PLC controller. Includes operator keypad and text display for operation, maintenance and troubleshooting
- › NEMA 4 rated electrical enclosure with UL listed control panel
- › Fused control voltage transformer
- › Hour meter and temperature switch
- › Pressure sensors for oil pressure and final pressure
- › Emergency stop push button
- › Audible alarm
- › Ambient temperature range 40° to 113° F
- › 12 month warranty

### Verticus models

- › Interstage pressure gauges
- › Sound attenuated enclosure  
MINI VERTICUS: 70 dBA    MAXI VERTICUS: 79 dBA

### AVAILABLE ACCESSORIES

- › BAUER air purification system with SECURUS
- › Interstage pressure gauges (VERTECON only)
- › TEFC motor
- › Machine feet
- › Extended base for compressor and 2 storage cylinders

### DIMENSIONS L x W x H inches (mm)

- › VERTECON 45 x 32.5 x 55 (1143 x 826 x 1397)
- › MINI VERTICUS 49.5 x 29.5 x 58 (1257 x 749 x 1473)
- › MAXI VERTICUS 52 x 34 x 65.5 (1321 x 864 x 1664)

### WEIGHT pounds (kg)

- › VERTECON 550 - 660 (250 - 300)
- › MINI VERTICUS 880 - 950 (400 - 432)
- › MAXI VERTICUS 1100 - 1225 (500 - 556)

## Technical Data

Model	Capacity FAD <sup>1)</sup>		Number of stages	Motor		Drive	Recommended purification system
	scfm	l/min		hp	kw		
<b>5000 psig (345 bar)</b>							
100	5	142	3	5	3.7	E1 / E3	P2 SECURUS
120	7.3	207	3	7.5	5.5	E1 / E3	P2 SECURUS
15.1	11.5	325	4	10	7.5	E1 / E3	P5 SECURUS
150	17.5	500	4	15	11	E3	P5 SECURUS
180	22	623	4	20	15	E3	P10 SECURUS
<b>6000 psig (414 bar)</b>							
100H	3.5	100	3	5	3.7	E1 / E3	P2 SECURUS
12.4	8.6 - 10.5	244 - 300	4	7.5 - 10	5.5 - 7.5	E1 / E3	P5 SECURUS
15.11 <sup>2)</sup>	15	425	4	15	11	E3	P5 SECURUS
18.1 <sup>2)</sup>	20	566	5	20	15	E3	P10 SECURUS

1) Compressor capacity (FAD) is referenced to standard inlet conditions and 80% of the compressor's maximum working pressure. Tolerance +/- 5%.

2) Models 15.11 and 18.1 available for 7000 psig.

E1 = 230 / 1 / 60    E3 = 230 - 460 / 3 / 60    Other voltages and frequencies available upon request.    Engine driven models available.

Dimensions and weight are approximate and are dependent upon model and drive.

### BAUER COMPRESSORS INC.

1328 Azalea Garden Road | Norfolk, VA 23502

TEL. +1 (757) 855-6006

FAX +1 (757) 857-1041

sls@bauercomp.com

www.bauercomp.com



BAUER COMPRESSORS INC.  
Norfolk, Virginia is  
registered to ISO 9001

### VERTICAL DESIGNS

172.08.11.1SP

subject to alteration without notice or obligation